



USB3.0 male plug with cable (single rubber coating)



USB3.0 female socket (without cable)



YU-USB3-JSX-01-001


- 1: Independent USB3.0 socket design, easy to install and operate
- 2: Achieve double-headed male to female adapter, snap locking, ensure safe and stable
- 3: Cable can be customized
- 4: Compatible with USB2.0, protection level IP67
- 5: Sheath of cable protect cable outlet well
- 6: Solid connections system can provide the solutions for data transmission in harsh environments



male plug + female socket with cable 1M



YU-USB2-JSX-01-001



1/2 bayonet connect




Gold-plated copper contact




YU-USB SERIES SPECIFICATIONS SHEET


PICTURE AND PART NO.




YU-USB3-CPI-01-100
USB3.0 male plug with cable
(single rubber coating)




YU-USB3-CPI-02-100
USB3.0 male plug with cable
(Double rubber coating)




YU-USB3-JSX-01-001
USB3.0 female socket



YU-USB2-CPI-01-100
USB2.0 male plug with cable
(single rubber coating)



YU-USB3-JSX-03-100
Male plug+female socket
with cable 1M



YU-USB2-JSX-01-001
USB2.0 female socket

Cable specification	0.15m m ² ~ 0.2m m ² /26-24 AWG
Diameter range	Φ5.5mm ~ Φ7mm
Contact diameter × number	9
Rated Current (A)	1.5A
Contact resistance	<30mΩ
Withstanding Voltage (AC.V) 1 minute	1000V、2.0-500V、3.0-100V
Insulation resistance	> 500MΩ
Protection level	IP67
Durability	> 500times
Working temperature	-40°C ~ 80°C
Connecting mode	Quickly bayonet connect

MATERIALS	
Housing, the insulating parts	High-performance engineering plastics
Hardware	Zinc Alloy (pearl hard chrome)
Copper needles	Copper Shell
Waterproof circle	Silica gel
Flammability rating	UL94-V0

CONNECTION SCHEMES



DIMENSION FIGURE

